

Add RSTOR S3 to Cohesity

November 2020 Prepared by: RSTOR Support

RSTOR

Table of Contents

1	Configuration Steps	3



1 Configuration Steps

To add RSTOR S3 to Cohesity complete the following steps.

- 1. First, open your RSTOR portal and click on your profile icon in the upper right-hand corner. Select "MY ACCOUNT".
- 2. Under your account page, click on "+ GENERATE KEY".
- 3. Once your key is generated you will later be prompted to copy the keys from this pop-up box. Write down both the access key and secret key as you will not be able to access them again after hitting "OK".
- 4. From the Cohesity interface, navigate to "Protection".
- 5. Click on "Register External Target" in the upper right-hand corner.

COHESITY cohesity-01 ~	Dashboard	Protection	Platform	Admin	○ H ? Q 8
External Targets					Register External Target
Targets Settings					

6. For purpose, select "Archive". Add the bucket name, newly generated keys, and endpoint. For the endpoint section of this set-up, every endpoint is going to be specifically tailored to your company. The URL is typically "s3.CompanyName.rstorcloud.io". When finished, click "Register". To have a backup job archive to the "RSTOR" Archive, either edit an existing policy, or create a new one and set the rules for archival.

COHESITY cohesity-01 ~	Dashboard	Protection	Monitoring	Platform	Admin	More 🗸	H G	8
New Target: RStor 🛞	Description							
Purpose Archival Tiering Type \$3 Compatible	•							
Bucket Name * BUCKETNAME								
Access Key ID * AccessKeyld								
Secret Access Key *								
Endpoint * s3.demo.rstorcloud.io								
Secure Connection (HTTP5) Register Cancel								